

Chewing gum remover POLY-4

Pressure max.	5100 psi
Spray angle	Point jet
Temperature max.	205 °F
Housing	Brass (nickel-plated)
Nozzle-type	Poly nozzles
Nozzle-size	030 - 080
Flow rate max.	34 l/min
Length / Diameter	113 mm / Ø 38 mm
Weight	600 g



Size	M22 M	G 1/4 F	M18 F	Repair kit
030	99.9763.030	99.9761.030	99.9764.030	66.9761.030
035	99.9763.035	99.9761.035	99.9764.035	66.9761.030
040	99.9763.040	99.9761.040	99.9764.040	66.9761.030
045	99.9763.045	99.9761.045	99.9764.045	66.9761.030
050	99.9763.050	99.9761.050	99.9764.050	66.9761.030
055	99.9763.055	99.9761.055	99.9764.055	66.9761.030
060	99.9763.060	99.9761.060	99.9764.060	66.9761.030
065	99.9763.065	99.9761.065	99.9764.065	66.9761.030
070	99.9763.070	99.9761.070	99.9764.070	66.9761.030
075	99.9763.075	99.9761.075	99.9764.075	66.9761.030
080	99.9763.080	99.9761.080	99.9764.080	66.9761.030

Description

The cleaning head can be fitted with up to 18 fine nozzles with maximum 350 bar operating pressure. The device is hand-held or used as an accessory for the removal of chewing gum and other stubborn dirt. The chewing gum remover POLY-2 can be used on smooth surfaces with cold water or hot water up to 205 °F. Rough surfaces are cleaned with hot water at 185-205 °F.