
**PREMIUM**SELF-PRIMING  
PUMPSPER MAGGIORI  
INFORMAZIONI

DIMENSIONI IMBALLO (cm)	145 x 134 x 150
QUANTITÀ BANCALE	1
DIMENSIONI BANCALE (cm)	145 x 134 x 150
N. MACCHINE IN BOX DA 20'	4
N. MACCHINE IN BOX DA 40' (40' HQ)	8

Cassa in legno non ottimizzata

# FDX HOT CUBE XL

## SKID

**RW PREMIUM**Pompa con 3 pistoni in  
ceramica e testata in ottone**TW PREMIUM**Pompa con 3 pistoni in  
ceramica e testata in ottonePannello di controllo  
professionaleSistema di pompaggio  
diretto dell'acqua con  
filtro autopulente e  
pompa anticalcare**CARATTERISTICHE GENERALI**

- Idropulitrice professionale a caldo per utilizzo senza allacciamento alla rete elettrica
- Serbatoio Diesel 45 lt con galleggiante livello e filtro di riempimento
- Caldaia verticale in acciaio inox ad alto rendimento con serpentina a doppia spirale
- Sistema elettronico di regolazione della temperatura con basso pendolamento del valore impostato
- Bruciatore azionato da Flussostato
- Valvola di sicurezza
- Protezione termica della caldaia
- Kit comando controllo fiamma
- Motore Diesel Kohler KDW1003 (26HP)
- Pompe Comet TW / RW Premium
- Riduttore di giri (con pompa 1450 rpm)
- Avviamento elettrico
- Contatore
- Regolatore manuale di giri
- Valvola regolazione professionale a ripristino graduale della pressione
- Valvola termostatica
- Filtro acqua di grande dimensione in ingresso pompa a cartuccia ispezionabile
- Opzione aspirazione acqua da serbatoio esterno
- Adatto per un uso altamente professionale

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODICE	MODELLI	POMPA	MAX		WORK		WORK l/h	°C	HP kW		kg/h	kg	(L x W x H) cm
			bar	MPa	bar	MPa			HP	kW			
36033-00006	FDX Hot Cube XL 23/250	RW	250	25	30÷240	3÷24	400÷1380	85÷110	26	19,3	8,0	450	125 x 85 x 105
36033-00007	FDX Hot Cube XL 18/350	TW	350	35	50÷335	5÷33,5	320÷1080	85÷110	26	19,3	8,0	450	125 x 85 x 105
36033-00008	FDX Hot Cube XL 30/200	TW	200	20	30÷190	3÷19	710÷1800	85÷110	26	19,3	8,5	450	125 x 85 x 105

DOTAZIONE STANDARD



Pistola GH 955 con Swivel

CARATTERISTICHE TECNICHE					MODELLI COMPATIBILI		
l/min	IN	OUT	bar	CODICE	36033-00006	36033-00007	36033-00008
40	G 3/8" M	M22x1,5F long	400	<b>00080-01094</b>			
40	G 3/8" M	M24x1,5F long	400	<b>00080-01095</b>			



Lancia dritta con portaugello, senza ugello

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	OUT	mm	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 M	1/4" NPT F	1200	<b>10002-04016</b>			
M24x1,5 M	1/4" NPT F	1200	<b>10002-04017</b>			



Ugello con getto a lama

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	Ø		CODICE	36033-00006	36033-00007	36033-00008
1/4" NPT M	055	25	<b>00080-01378</b>			
1/4" NPT M	04	15	<b>00080-01368</b>			
1/4" NPT M	09	25	<b>00080-01363</b>			



Kit tubo gomma mandata

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	OUT	m	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 F - Ø14	G 3/8" F	10 - R2 3/8"	<b>10002-03562</b>			
M24x1,5 F	G 3/8" F	10 - R2 3/8"	<b>10002-04013</b>			



Kit comando controllo fiamma

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
CODICE				36033-00006	36033-00007	36033-00008
<b>10001-00953</b>						

DOTAZIONE STANDARD



Filtro acqua autopulente

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	OUT	mesh	CODICE	36033-00006	36033-00007	36033-00008
G 1" F	G 1" F	50	<b>00070-00190</b>			



Cartuccia per filtro acqua

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	OUT	mesh	CODICE	36033-00006	36033-00007	36033-00008
-	-	50	<b>00070-00191</b>			

ACCESSORI



Lancia dritta con ugello rotante

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	OUT	mm	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 M	1/4" F NPT	1220	<b>10002-04023</b>			
M24x1,5 M	1/4" F NPT	1220	<b>10002-04113</b>			



Kit lancia sabbiante/bicarbonato professionale

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	mm	Ø	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 M	580 / 700	055	<b>10002-03485</b>			
M24x1,5 M	580 / 700	040	<b>10002-04026</b>			
M22x1,5 M	580 / 700	090	<b>10002-03486</b>			



Lancia schiumogena, con regolatore (max 60°C)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	l/min	lt	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 M	20	1	<b>10002-04065</b>			
M24x1,5 M	20	1	<b>SU RICHIESTA</b>			



Sonda spurgatubi

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	m	l/min	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 M	25	16 ÷ 29	<b>00058-00630</b>			
M22x1,5 M	25	30 ÷ 42	<b>00058-00634</b>			




Kit sonda spurgatubi con attacchi rapidi M24x1,5 (350 bar)

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	m	l/min	CODICE	36033-00006	36033-00007	36033-00008
M24x1,5 M	25	16 ÷ 29	<b>00058-00651</b>			




Kit prolunga tubo mandata in gomma

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
IN	OUT	m	CODICE	36033-00006	36033-00007	36033-00008
M22x1,5 Ø14	M22x1,5 Ø14	10 - R2 3/8"	<b>10002-03564</b>			
M24x1,5	M24x1,5	10 - R2 3/8"	<b>10002-04024</b>			



Convogliatore di fumi esausti camino

CARATTERISTICHE TECNICHE				MODELLI COMPATIBILI		
Ø	kg	-	CODICE	36033-00006	36033-00007	36033-00008
200	1,4	-	<b>00032-00095</b>			



# FDX HOT CUBE XL

## SKID

**PREMIUM**

**SELF-PRIMING PUMPS**



**RW PREMIUM**

Pump with 3 integral ceramic pistons and brass pump head



**TW PREMIUM**

Pump with 3 integral ceramic pistons and brass pump head



Professional control panel



FOR MORE INFORMATION




BOX DIMENSION (cm)	145 x 134 x 150
QUANTITY FOR PALLET	1
PALLET DIMENSION (cm)	145 x 134 x 150
N. MACHINES CONTAINER 20'	4
N. MACHINES CONTAINER 40' (40' HQ)	8

Wooden case not optimized



Direct water pumping system with self-cleaning filter and antiscaling pump



### GENERAL FEATURES

- Professional hot water high pressure cleaner for uses without connection to electricity grid
- 45 lt Diesel tank with level float and fill up filter
- Double coil high efficiency boiler with stainless steel outer casing
- Electronic temperature setting system with constant water temperature
- Flow-switch operated burner
- Safety valve
- Boiler thermal protection
- Flame control kit
- Kohler KDW1003 Diesel liquid cooled engine (26HP)
- Premium Comet TW / RW pumps
- Gearbox (with 1450 rpm pump)
- Electrical starting
- Hours meter
- RPM manual regulator
- Stainless steel gradual pressure restoration valve with EASY START
- Thermostatic valve
- Big water filter at pump inlet, readily serviceable cartridge type
- Water suction from external tank option
- Suitable for high professional use

### TECHNICAL FEATURES

CODE	MODELS	PUMP	MAX		WORK		WORK l/h	°C	HP kW		kg/h	kg	(L x W x H) cm
			bar	MPa	bar	MPa			HP	kW			
36033-00006	FDX Hot Cube XL 23/250	RW	250	25	30÷240	3÷24	400÷1380	85÷110	26	19,3	8,0	450	125 x 85 x 105
36033-00007	FDX Hot Cube XL 18/350	TW	350	35	50÷335	5÷33,5	320÷1080	85÷110	26	19,3	8,0	450	125 x 85 x 105
36033-00008	FDX Hot Cube XL 30/200	TW	200	20	30÷190	3÷19	710÷1800	85÷110	26	19,3	8,5	450	125 x 85 x 105

### STANDARD EQUIPMENT



TECHNICAL FEATURES					COMPATIBLE MODELS		
l/min	IN	OUT	bar	CODE	36033-00006	36033-00007	36033-00008
40	G 3/8" M	M22x1,5F long	400	<b>00080-01094</b>			
40	G 3/8" M	M24x1,5F long	400	<b>00080-01095</b>			



TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	OUT	mm	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 M	1/4" NPT F	1200	<b>10002-04016</b>			
M24x1,5 M	1/4" NPT F	1200	<b>10002-04017</b>			



TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	∅		CODE	36033-00006	36033-00007	36033-00008
1/4" NPT M	055	25	<b>00080-01378</b>			
1/4" NPT M	04	15	<b>00080-01368</b>			
1/4" NPT M	09	25	<b>00080-01363</b>			



TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	OUT	m	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 F - Ø14	G 3/8" F	10 - R2 3/8"	<b>10002-03562</b>			
M24x1,5 F	G 3/8" F	10 - R2 3/8"	<b>10002-04013</b>			



TECHNICAL FEATURES				COMPATIBLE MODELS		
CODE				36033-00006	36033-00007	36033-00008
<b>10001-00953</b>						

STANDARD EQUIPMENT



Self cleaning water filter

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	OUT	mesh	CODE	36033-00006	36033-00007	36033-00008
G 1" F	G 1" F	50	<b>00070-00190</b>			



Cartridge for water filter

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	OUT	mesh	CODE	36033-00006	36033-00007	36033-00008
-	-	50	<b>00070-00191</b>			

ACCESSORIES



Straight lance with rotating nozzle

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	OUT	mm	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 M	1/4" F NPT	1220	<b>10002-04023</b>			
M24x1,5 M	1/4" F NPT	1220	<b>10002-04113</b>			



Professional Sand/Soda blasting lance kit

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	mm	∅	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 M	580 / 700	055	<b>10002-03485</b>			
M24x1,5 M	580 / 700	040	<b>10002-04026</b>			
M22x1,5 M	580 / 700	090	<b>10002-03486</b>			



Foam lance, with regulator (max 60°C)

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	l/min	lt	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 M	20	1	<b>10002-04065</b>			
M24x1,5 M	20	1	<b>ON REQUEST</b>			



Drain nozzle

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	m	l/min	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 M	25	16 ÷ 29	<b>00058-00630</b>			
M22x1,5 M	25	30 ÷ 42	<b>00058-00634</b>			




Drain nozzle kit with quick coupler M24x1,5 (350 bar)

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	m	l/min	CODE	36033-00006	36033-00007	36033-00008
M24x1,5 M	25	16 ÷ 29	<b>00058-00651</b>			



Rubber delivery hose extension kit

TECHNICAL FEATURES				COMPATIBLE MODELS		
IN	OUT	m	CODE	36033-00006	36033-00007	36033-00008
M22x1,5 Ø14	M22x1,5 Ø14	10 - R2 3/8"	<b>10002-03564</b>			
M24x1,5	M24x1,5	10 - R2 3/8"	<b>10002-04024</b>			



Exhausted fume conveyor

TECHNICAL FEATURES				COMPATIBLE MODELS		
Ø	kg	-	CODE	36033-00006	36033-00007	36033-00008
200	1,4	-	<b>00032-00095</b>			